

LEDI 6/S 3U



Red LED 7segment display
Hour and minute: 70 mm
Second: 50 mm.

Legible up to 30 meters. Manual adjust luminosity
Ni-Mh batteries providing over 2 day operation in the event of mains failure

AFNOR NFS 87500 time code receiver clock

Power supply 230 VAC/50-60Hz. 6VA, class 2.

Operating temperature range : -20 to +70°C.

RACK 19" 3U. Dimensions : 482x132x265 mm.

Net weight 7kg

Complies to EMC Directive 98/366 EEC including directive 93/68.

EN 55024, EN 55022, EN 60950

		ITEM CODE				
		9	2	2	4	
		↑	↑	↑	↑	
VERSION						
AFNOR NFS 87500/IRIG B time code receiver clock	<input checked="" type="checkbox"/>	8				
NTP input – Ethernet 10/100 base T	<input checked="" type="checkbox"/>	N				
SMPTE-EBU time code receiver clock	<input checked="" type="checkbox"/>	7				
COLOUR OF LED						
Red	<input checked="" type="checkbox"/>	1				
Green	<input checked="" type="checkbox"/>	2				
Yellow	<input checked="" type="checkbox"/>	3				
ALTUGLASS FRONT FACE						
Standard	<input checked="" type="checkbox"/>			S		
No reflective	<input checked="" type="checkbox"/>			A		
POWER SUPPLY						
Standard : 230VAC/50-60Hz	<input checked="" type="checkbox"/>				0	
115VAC/50-60Hz	<input checked="" type="checkbox"/>				1	
18 to 72 VDC	<input checked="" type="checkbox"/>				9	