

LEDI® WORLD REVERSO 7

Double face



Matt anodized aluminum case

Set of 2, 3, 4, 5, 6 or 7, LEDI® 7 digital clocks displaying local times of cities in the world.

Name of cities are inscribed in white letters below respective digital clock. (Name of cities must be specified at the firm order).

Legible up to 35 meters.

Manual setting of different time zones and Daylight Saving Timing.



Time Setting

The professional LEDI® clocks can display the same time information, synchronized by a master clock or a time server.


Internal time base

The LEDI® clock has its own temperature compensated TCXO time base which allows an accuracy about 0.1 sec/day between 0° et 40°C in case of synchronization loss.

Security

Backup of time information in case of mains absence, by lithium battery : 10 years

Specification

Power supply	230VAC/50-60Hz 115VAC/50-60Hz Version NTP : POE (Power Over Ethernet)
Certification	CE, EN 60950, EN 55022, EN 55024, ROHS
Maximum consumption	35 VA
IP	40
MTBF	56 225 h.
MTTR	Display: 5 min. CPU: 5 min. Power supply : 5 min.
Weight	-
Dimension	Refer to "TIME ZONE" and drawing on next page Mounting bracket : 150 mm
Digit height	Hour/minute: 70 mm
Maximal distance of legibility	35 meters
Shock resistance	IK9
Operating temperature	-20° to 50°C
Electrical equipment classification	Class 2 

Key feature

Perfectly silent, direct and accurate reading of time.
SMD bi-colour LED technology allows changing each time zone colour independently in red, green or yellow (optional: white or blue).
The patented technology of the light guide provides a perfect regularity of the brightness and viewing angle at 160°.
The front face of the LEDI® is coated with an antiglare and anti-scratch film giving an extraordinary 60000:1 level of contrast.
A protection against over-voltage and industrial interference via EMC filter.
An easy "plug-and-play" installation.
 Matt anodized aluminum case:

Double face IP40.

Its participation in the sustainable development, life span over 20 years.
2 years warranty.

Remote management (with NTP synchronization)

Remote configuration and time setting via WEB interface.
 Time zone setting and automatic daylight saving time change.
 Supervision via HTTP, SNMP, Telnet. "GT Network Manager" (software Windows® NT/XP/2000/Vista 32 bits/Windows 7).

Synchronization inputs

- **Standalone TCXO quartz time base synchronizable by:**
- DCF(EUROPE).
- France Inter (EUROPE).
- GPS.
- AFNOR NFS 87500
- IRIG B : shall be specified on Purchase order.
- NTP Ethernet 10/100BaseT détection automatique : RJ45.
- NTP POE (Power Over Ethernet).
- Wi-Fi (IEEE 802.11 B/G standard).

Display / LED specifications

Simple row LED display.
SMD Technology, viewing Angle: 160°.

Bi-colored LED (red green)		Monochrome LED
Red : 245 mcd	Yellow	Blue : 625 mcd
Green : 780 mcd		White : 625 mcd

LEDI® WORLD REVERSO 7

Double face

ITEM CODE							
ND57	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	↑	↑	↑	↑	↑	↑	↑

TIME ZONE DISPLAY																				
2 Time zones	Dimensions: L690 x H210 x D99 mm	2																		
3 Time zones	Dimensions: L1035 x H210 x D99 mm	3																		
4 Time zones	Dimensions: L1380 x H210 x D99 mm	4																		
5 Time zones	Dimensions: L1720 x H210 x D99 mm	5																		
6 Time zones	Dimensions: L2060 x H210 x D99 mm	6																		
7 Time zones	Dimensions: L2400 x H210 x D99 mm	7																		

DISPLAY																				
Double face	<input checked="" type="checkbox"/>	2																		

VERSION																				
France Inter Radiosynchronization. Antenna + 4m of cable	<input checked="" type="checkbox"/>	F																		
DCF Radiosynchronization. Antenna + 4m of cable	<input checked="" type="checkbox"/>	D																		
GPS Antenna + 10m of cable	<input checked="" type="checkbox"/>	G																		
AFNOR NFS 87500* UTC. receiver clock	<input checked="" type="checkbox"/>	8																		
AFNOR NFS 87500* LOCAL. receiver clock	<input checked="" type="checkbox"/>	9																		
NTP Ethernet 10/100 base T Synchronization	<input checked="" type="checkbox"/>	N																		
Wi-Fi (IEEE 802.11 B/G standard)	<input checked="" type="checkbox"/>	W																		

*IRIG.B Version : to be specified as « remark » on your Purchase Order.

CONFIGURABLE LED																				
Configurable colour: red, yellow, green	<input type="checkbox"/>	1																		
Configurable colour : white or blue	<input checked="" type="checkbox"/>	5																		

MOUNTING																				
With ceiling mount bracket	<input checked="" type="checkbox"/>	P																		

COLOUR OF CASE																				
Standard : anodised aluminum	<input type="checkbox"/>	7																		
Black painted aluminum	<input checked="" type="checkbox"/>	0																		
Specific	<input checked="" type="checkbox"/>	-																		

POWER SUPPLY																				
Standard : 230VAC/50-60Hz	<input checked="" type="checkbox"/>	0																		
115VAC/50-60Hz	<input checked="" type="checkbox"/>	1																		
Power Over Ethernet (POE) 1 cable for 2 to 3 time zones	<input checked="" type="checkbox"/>	7																		
Power Over Ethernet (POE) 2 cable for 4 to 6 time zones	<input checked="" type="checkbox"/>	8																		
Power Over Ethernet (POE) 3 cables for 7 time zones	<input checked="" type="checkbox"/>	9																		

OPTIONS																				
Tropicalized	<input checked="" type="checkbox"/>	U																		
Stop clock function via WEB interface	<input checked="" type="checkbox"/>	F																		
*Removable magnetic plate + fixed city name	<input checked="" type="checkbox"/>	G																		
*Removable magnetic plate with adhesive layer (to use with an erasable marker pen)	<input checked="" type="checkbox"/>	P																		
Specification	<input checked="" type="checkbox"/>	S																		

*Allows the change of city name.

